

Slitters, Rewinders, Die Cutters

DIE CUTTERS

- Servo-driven re-registration module with a 40" diameter unwind, electronic sensor and user-friendly touch-screen control panel.
- Pneumatically inflatable 3" Diameter unwind, reversible dual-rewind and waste wind up spindles.
- Interchangeable slitting station module with choice of rotary shear or razor cutting
(pneumatic crush- optional)
- Two fully supported and dual side-framed die stations, complete with fully hardened anvil rolls and die blocks.
- Ultra-sonic web guide for converting both clear and opaque materials.
- Programmable incremental counter.
- Heavy-duty 5 hp AC variable speed motor with two 1 hp DC clutch-less motor drives.
- Synchronized inspection strobe light.
- Fan folder and conveyor ready.

SLITTERS / REWINDERS

- Proven smooth running and reliable clutchless drive.
- Rewinds numerous substrates including thin, unsupported films.
- Adjustable splice table at unwind.
- Adjustable electronic web tension control.
- Choice of either left-right or right-left web path.
- Reversible rewind(s) for over or under winding.
- Interchangeable slitting station module with choice of rotary shear or razor(pneumatic crush extra)
- 40" (1016mm) max. diameter unwind with heavy-duty pneumatic disc brake.
- 24" (609mm) max. diameter rewind(s) with E-Z change spindle(s)
- Programmable incremental counter.
- Ultrasonic web guide.

DUAL SPINDLE REWIND

- Rewinds numerous substrates including thin, unsupported films.
- Adjustable splice table at unwind.
- Adjustable electronic web tension control.

- Choice of either left-right or right-left web path.
- Reversible rewind(s) for over or under winding.
- Interchangeable slitting station module with choice of rotary shear or razor(numatic crush extra)
- 40" (1016mm) max. diameter unwind with heavy-duty pneumatic disc brake.
- 24" (609mm) max. diameter rewind(s) with E-Z change spindle(s)
- Programmable incremental counter.
- Ultrasonic web guide.
- Proven smooth running and reliable clutchless drive.

REWIND / INSPECTION TABLES

- Web width 7" & 10" (178mm, 254mm)
- Unwind Capacity = 14" (610) or 30" (762mm)
- Rewind Capacity 18" (457mm) or 24" (610mm)
- Dual Quick-Change 3" OD Air Cores
- Variable speed control, hand and foot
- Reverse rewind
- Unwind tension control
- HMI display panel
- Incremental label counter or Individual/Incremental label count sensor
- 24" x 48" or 30" x 60" stainless steel top
- 1.5 HP heavy duty motor
- 20 AMP, 115 VAC, VFD AC Drive
- PLC "Programmable Logic Control"

UNWIND STAND-DT SERIES

Standard Features:

- Left to Right or Right to left Operation (specify when ordering)
- 3010 Model 36" length, 12" wide, 24" height
- 3" pneumatic Core Holder
- "Set it and Forget it" Tension Control
- 2 1/4" diameter aluminum idler rollers mounted on 1" shafts

- Sealed ball bearings on main shaft and idler rollers
- Double the capacity of Mark Andy 800 series presses
- Constant Tension with "dancer" auto compensation
- Other sizes available

MOBILE ROLL HANDLING EQUIPMENT

Standard Features:

- 800lb. lift capacity with 63" or 81" lift height
- Manual winch with automatic safety brake
- Heavy-duty casters for smooth easy rolling